

EC-311

1. Product and company identification

Product Name: EC-311

Product Use: Coating/wood protection

Manufacturer/Supplier: Nano Faraz Sepahan Co.

Unit No.3, Fanafarini 2 building, Isfahan

Science & technology Town, Isfahan

University of Technology Blvd, Isfahan, IRAN

Phone Number: +983133932431

Emergency Phone: +989130844702

Date of Preparation: 02/19/2019

2. Hazards identification

EMERGENCY OVERVIEW

CAUTION

FLAMMABLE, IRRITATING TO EYES, IRRITATING TO SKIN.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: Irritating to eyes - potentially severe.

Skin: No skin irritation

Most important symptoms and effects, both acute and delayed irritant effects,

respiratory paralysis, Dizziness, inebriation, euphoria, Nausea, Vomiting, narcosis

Potential Environmental Effects: Do not let product enter drains.

Risk of explosion.



EC-311

3. Composition/information on ingredients

ingredient	CAS number	Proportion.
Ethanol	64-17-5	40-70%
Ethyl silicate	78-10-4	3-10%
Alkoxy silanes & siloxanes	n/a	5-20%
Organotin compound	64-19-7	0.3-5%

4. First-aid measures

Eye Contact: After eye contact rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

Skin Contact: In case of skin contact take off immediately all contaminated clothing. Rinse skin with water/ shower.

Inhalation: If breathed in, move person into fresh air.

Ingestion: immediately make victim drink water (two glasses at most). Consult a physician.

5. Fire-fighting measures

Flammability: Flammable

Protection of Firefighters: Special protective equipment for firefighters In the event of

fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal Precautions: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, and consult an expert.



EC-311

Environmental Precautions: Do not let product enter drains. Risk of explosion. **Methods for Containment and Clean-Up:** Cover drains. Collect, bind, and pump off spills. Take up with liquid-absorbent material. Dispose of properly. Clean up affected area.

7. Handling and storage

Handling: Observe label precautions. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge. Change contaminated clothing. Wash hands after working with substance. Always comply with health and safety regulations.

Storage: Store in original container. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Keep away from oxidizing agents, strong alkaline and acids.

No smoking. Containers which have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature: 5- 35°C

8. Exposure controls/personal protection

Personal Protective Equipment:

Eye/Face Protection: Wear approved eye protection (splash-proof chemical safety goggles) and face protection (face shield). Do NOT wear contact lenses when using this product.

Hand Protection: Wear suitable gloves - nitrile, rubber.

Skin and Body Protection: Wear suitable protective clothing.



EC-311

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

9. Physical and chemical properties

Form liquid

Appearance: Clear

Colorless

Odor: Alcohol-like

Density: 0.80 gr/cm³

Flash Point: 20-25 °C

Pour point: -30 °C

10. Stability and reactivity

Stability: The product is chemically stable under standard ambient conditions (room temperature).

Conditions of Reactivity: Vapors may form explosive mixture with air.

Incompatible Materials: rubber, various plastics

Possibility of Hazardous Reactions:

Risk of explosion/exothermic reaction with:

hydrogen peroxide, perchlorates, perchloric acid, Nitric acid, mercury(II) nitrate, permanganic acid, Nitriles, peroxide compounds, Strong oxidizing agents, nitrosyl compounds, Peroxides, sodium, Potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metallic oxides, uranium hexafluoride, iodides, Chlorine, Alkali metals,



EC-311

Alkaline earth metals, alkali oxides, Ethylene oxide, silver, with, Nitric acid, silver compounds, with, Ammonia, potassium permanganate, with, conc. sulfuric acid Risk of ignition or formation of inflammable gases or vapours with:

Halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, Fluorine, hydrides, Oxides of phosphorus, platinum, Nitric acid, with, potassium permanganate

11. Toxicological information

Acute oral toxicity: Symptoms: Nausea, Vomiting

Acute inhalation toxicity: Symptoms: Possible damages: mucosal

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to

degreasing properties of the product.

Eye irritation: Causes serious eye irritation.

12. Ecological information

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

13. Disposal considerations

Disposal Instructions: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.



EC-311

14. Transport information

TDG Classification:

UN1170; flammable; Class 3; PG II

15. Regulatory information

EU regulations Major Accident Hazard SEVESO III

Legislation FLAMMABLE LIQUIDS

P₅c

Quantity 1: 5.000 t

Quantity 2: 50.000 t

Occupational restrictions Take note of Dir 94/33/EC on the

protection of young people at work.

Regulation (EC) No 1005/2009 on not regulated

substances that deplete the ozone layer not regulated

Substances of very high concern (SVHC) This product does not contain substances

of very high concern according to

Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory

concentration limit of ≥ 0.1 % (w/w).

Labeling

Hazard pictograms







16. Other information

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Version #: 1.0

Prepared by: Nano faraz sepaha Co.

Phone: +98(0)3133932431

www.nanofaraz.com